Package: DiscriMiner (via r-universe)

November 13, 2026

Type Package

Title Tools of the Trade for Discriminant Analysis

Version 0.1.29.9001

Depends R (>= 2.15.0)

Imports graphics, stats, utils

Suggests MASS, FactoMineR

Description Functions for Discriminant Analysis and Classification purposes. Covers various methods such as descriptive, geometric, linear, quadratic, PLS, as well as qualitative discriminant analyses. Compatibility updates by Renova.

License GPL-3

URL http://www.gastonsanchez.com

LazyData yes

Collate 'DiscriMiner-package.R' 'FRatio.R' 'betweenCov.R' 'betweenSS.R' 'binarize.R' 'classify.R' 'corRatio.R' 'desDA.R' 'discPower.R' 'disqual.R' 'easyMCA.R' 'geoDA.R' 'getWithin.R' 'groupMeans.R' 'groupMedians.R' 'groupQuants.R' 'groupStds.R' 'groupVars.R' 'linDA.R' 'my_betweenCov.R' 'my_catDA.R' 'my_discFunctions.R' 'my_geoDA.R' 'my_groupMeans.R' 'my_linDA.R' 'my_mca.R' 'my_plsDA.R' 'my_quaDA.R' 'my_tdc.R' 'my_verify.R' 'my_withinCov.R' 'plot.plsda.R' 'print.desda.R' 'print.disqual.R' 'print.geoda.R' 'print.linda.R' 'print.plsda.R' 'print.quada.R' 'print.qualmca.R' 'quaDA.R' 'totalCov.R' 'totalSS.R' 'withinCov.R' 'withinSS.R' 'my_plsDA_old.R' 'plsDA_old.R' 'plsDA.R'

Author Gaston Sanchez [aut, cre], Charles Determan [ctb]

Maintainer Gaston Sanchez <gaston.stat@gmail.com>

NeedsCompilation no

Repository https://renova-r.r-universe.dev

Date/Publication 2026-11-13 17:54:14 UTC

RemoteUrl https://github.com/renova-r/DiscriMiner

RemoteRef renova-0.1.29.9001

RemoteSha 753357814306b00e02ff22aaf5dd7f9acbfbaf8c

Contents

DiscriMiner-package . . . 2
betweenCov . . . 3
betweenSS . . . 4
binarize . . . 5
bordeaux . . . 6
classify . . . 7
corRatio . . . 8
desDA . . . 9
discPower . . . 10
disqual . . . 12
easyMCA . . . 13
FRatio . . . 14
geoDA . . . 15
getWithin . . . 17
groupMeans . . . 18
groupMedians . . . 19
groupQuants . . . 20
groupStds . . . 21
groupVars . . . 22
infarctus . . . 23
insurance . . . 23
linDA . . . 24
plsDA . . . 26
quaDA . . . 28
totalCov . . . 30
totalSS . . . 31
withinCov . . . 32
withinSS . . . 33

Index **34**

`DiscriMiner-package` *Tools of the Trade for Discriminant Analysis*

Description

DiscriMiner contains several functions for Discriminant Analysis and Classification purposes covering various methods such as descriptive, geometric, linear, quadratic, PLS, as well as qualitative discriminant analyses.

Details

Package:	DiscriMiner
Type:	Package
Version:	0.1-23
Date:	2012-12-20
License:	GPL-3

Author(s)

Gaston Sanchez

Maintainer: Gaston Sanchez <gaston.stat@gmail.com>

References

http://www.gastonsanchez.com/discriminer

Lebart L., Piron M., Morineau A. (2006) *Statistique exploratoire multidimensionnelle*. Dunod, Paris.

Nakache J-P., Confais J. (2003) *Statistique explicative appliquee*. Editions Technip, Paris.

Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

Tenenhaus M. (1998) *La Regression PLS*. Editions Technip, Paris.

Tenenhaus M. (2007) *Statistique*. Dunod, Paris.

Tuffery S. (2008) *Data Mining et Statistique Decisionnelle*. Editions Technip, Paris.

Tuffery S. (2011) *Data Mining and Statistics for Decision Making*. Wiley, Chichester.

Multiple Correspondence Analysis and Related Methods. (2006) Edited by Michael Greenacre and Jorg Blasius. Chapman and Hall/CRC

`betweenCov` *Between-class Covariance Matrix*

Description

Calculates between-class covariance matrix

Usage

```
betweenCov(variables, group, div_by_n = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (No missing values are allowed)
group	vector or factor with group memberships (No missing values are allowed)
div_by_n	logical indicating division by number of observations

Details

When div_by_n=TRUE the covariance matrices are divided by n (number of observations), otherwise they are divided by n-1

Author(s)

Gaston Sanchez

See Also

getWithin, betweenSS, withinCov, totalCov

Examples

```
## Not run:
# load iris dataset
data(iris)

# between-class covariance matrix (dividing by n-1)
betweenCov(iris[,1:4], iris[,5])

# between-class covariance matrix (dividing by n)
betweenCov(iris[,1:4], iris[,5], div_by_n=TRUE)

## End(Not run)
```

---

betweenSS *Between-class Sum of Squares Matrix*

Description

Calculates between-class sum of squares and cross product matrix (a.k.a. between-class scatter matrix)

Usage

```
betweenSS(variables, group)
```

Arguments

variables	matrix or data frame with explanatory variables (No missing values are allowed)
group	vector or factor with group membership (No missing values are allowed)

Author(s)

Gaston Sanchez

See Also

betweenCov, withinSS, totalSS

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # between-class scatter matrix
  betweenSS(iris[,1:4], iris[,5])

## End(Not run)
```

---

binarize *Binarize a data frame into a super-indicator matrix*

Description

Convert a data frame with factors into a super-indicator matrix (a.k.a. complete disjunctive table from the french *tableau disjonctive complete*)

Usage

```
binarize(variables)
```

Arguments

variables	data frame with categorical variables (coded as factors)

Value

A super-indicator matrix of binary data

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

See Also

easyMCA

Examples

```
## Not run:
  # load insurance cars dataset
  data(insurance)

  # super-indicator matrix of binary data
  bin_insure = binarize(insurance[,-1])
  head(bin_insure)

## End(Not run)
```

---

bordeaux *Bordeaux Wines Dataset*

Description

Quality measures of wines from Bordeaux, France

Format

A data frame with 34 observations on the following 6 variables.

`year`	year of harvest
`temperature`	sum of daily average temperatures (in celsius degrees)
`sun`	duration of insolation (in hours)
`heat`	number of super-hot days
`rain`	rain level (in millimeters)
`quality`	wine quality: a factor with levels `bad`, `good`, and `medium`

References

Chapter 10: Analyse Discriminante, page 353.
Tenenhaus M. (2007) *Statistique*. Dunod, Paris.

Examples

```
## Not run:
  # load data
  data(bordeaux)

  # structure of data
  str(bordeaux)

## End(Not run)
```

`classify` *Classification function*

Description

Classify provided observations based on a given Discriminant object

Usage

```
classify(DA_object, newdata)
```

Arguments

`DA_object`	discriminant analysis object
`newdata`	vector or matrix or data frame with variables for which their classes will be calculated

Details

A `DA_object` is a discriminant analysis (DA) object obtained from a geometric predictive DA (class `"geoda"`), a linear DA (class `"linda"`), a quadratic DA (class `"quada"`), or a DISQUAL analysis (class `"disqual"`)

Value

A list with the following elements

`scores`	discriminant scores for each observation
`pred_class`	predicted class

Author(s)

Gaston Sanchez

See Also

`geoDA`, `linDA`, `quaDA`, `plsDA`, `disqual`

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # linear discriminant analysis
  my_lin1 = linDA(iris[,1:4], iris$Species)

  # select a sample of 15 observations
```

```
  set.seed(111)
  obs = sample(1:nrow(iris), 15)
  some_data = iris[obs, 1:4]

  # classify some_data
  get_classes = classify(my_lin1, some_data)
  get_classes

  # compare the results against original class
  table(iris$Species[obs], get_classes$pred_class)

## End(Not run)
```

`corRatio` *Correlation Ratio*

Description

Calculates the correlation ratio between a quantitaive variable and a qualitative variable

Usage

```
corRatio(variable, group)
```

Arguments

`variable`	a single quantitative variable
`group`	vector or factor with group memberships (qualitative variable)

Details

No missing values are allowed

Author(s)

Gaston Sanchez

References

Tenenhaus, M. (2007) *Statistique*. Dunod, Paris.

See Also

`FRatio`, `discPower`

Examples

```
## Not run:
  # iris dataset
  data(iris)

  # correlation ratio between Petal-Length and Species
  corRatio(iris$Petal.Length, iris$Species)

## End(Not run)
```

---

desDA *Descriptive Discriminant Analysis*

Description

Performs a Descriptive Discriminant Analysis (a.k.a. Factorial Discriminant Analysis from the french *Analyse Factorielle Discriminante*)

Usage

```
desDA(variables, group, covar = "within")
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group memberships
covar	character string indicating the covariance matrix to be used. Options are "within" and "total"

Details

When covar="within" the estimated pooled within-class covariance matrix is used in the calculations.
When covar="total" the total covariance matrix is used in the calculations.
The difference between covar="within" and covar="total" is in the obtained eigenvalues.

The estiamted pooled within-class covariance matrix is actually the within-class covariance matrix divided by the number of observations minus the number of classes (see getWithin)

Value

An object of class "desda", basically a list with the following elements

power	table with discriminant power of the explanatory variables
values	table of eigenvalues
discrivar	table of discriminant variables, i.e. the coefficients of the linear discriminant functions
discor	table of correlations between the variables and the discriminant axes
scores	table of discriminant scores for each observation

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

See Also

discPower

Examples

```
## Not run:
  # load bordeaux wines dataset
  data(bordeaux)

  # descriptive discriminant analysis with within covariance matrix
  my_dda1 = desDA(bordeaux[,2:5], bordeaux$quality)
  my_dda1

  # descriptive discriminant analysis with total covariance matrix
  my_dda2 = desDA(bordeaux[,2:5], bordeaux$quality, covar="total")
  my_dda2

  # plot factor coordinates with ggplot
  library(ggplot2)
  bordeaux$f1 = my_dda1$scores[,1]
  bordeaux$f2 = my_dda1$scores[,2]
  ggplot(data=bordeaux, aes(x=f1, y=f2, colour=quality)) +
  geom_hline(yintercept=0, colour="gray70") +
  geom_vline(xintercept=0, colour="gray70") +
  geom_text(aes(label=year), size=4) +
  opts(title="Discriminant Map - Bordeaux Wines (years)")

## End(Not run)
```

---

discPower *Discriminant Power*

Description

Measures Discriminant Power of explanatory variables

Usage

```
discPower(variables, group)
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group membership

Details

No missing values are allowed

Value

A data frame containing the following columns

correl_ratio	Correlation Ratios
wilks_lambda	Wilks Lambda
F_statistic	F-statistic
p_value	p-value of F-statistic

Author(s)

Gaston Sanchez

References

Tenenhaus M. (2007) *Statistique*. Dunod, Paris.

See Also

corRatio, FRatio

Examples

```
## Not run:
  # bordeaux wines dataset
  data(bordeaux)

  # discriminant power
  dp = discPower(bordeaux[,2:5], bordeaux$quality)
  dp

## End(Not run)
```

disqual *Discriminant Analysis on Qualitative Variables*

Description

Implementation of the DISQUAL methodology. Disqual performs a Fishers Discriminant Analysis on components from a Multiple Correspondence Analysis

Usage

```
disqual(variables, group, validation = NULL,
  learn = NULL, test = NULL, autosel = TRUE, prob = 0.05)
```

Arguments

variables	data frame with qualitative explanatory variables (coded as factors)
group	vector or factor with group memberships
validation	type of validation, either "crossval" or "learntest". Default NULL
learn	optional vector of indices for a learn-set. Only used when validation="learntest". Default NULL
test	optional vector of indices for a test-set. Only used when validation="learntest". Default NULL
autosel	logical indicating automatic selection of MCA components
prob	probability level for automatic selection of MCA components. Default prob = 0.05

Details

When validation=NULL there is no validation
When validation="crossval" cross-validation is performed by randomly separating the observations in ten groups.
When validation="learntest" validationi is performed by providing a learn-set and a test-set of observations.

Value

An object of class "disqual", basically a list with the following elements:

raw_coefs	raw coefficients of discriminant functions
norm_coefs	normalizaed coefficients of discriminant functions, ranging from 0 - 1000
confusion	confusion matrix
scores	discriminant scores for each observation
classification	assigned class
error_rate	misclassification error rate

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

Saporta G., Niang N. (2006) Correspondence Analysis and Classification. In *Multiple Correspondence Analysis and Related Methods*, Eds. Michael Greenacre and Jorg Blasius, 371-392. Chapman and Hall/CRC

See Also

easyMCA, classify, binarize

Examples

```
## Not run:
  # load insurance dataset
  data(insurance)

  # disqual analysis with no validation
  my_disq1 = disqual(insurance[,-1], insurance[,1], validation=NULL)
  my_disq1

  # disqual analysis with cross-validation
  my_disq2 = disqual(insurance[,-1], insurance[,1], validation="crossval")
  my_disq2

## End(Not run)
```

---

easyMCA *Multiple Correspondence Analysis*

Description

Performs a basic Multiple Correspondence Analysis (MCA)

Usage

```
easyMCA(variables)
```

Arguments

variables	data frame with categorical variables (coded as factors)

Value

An object of class "qualmca", basically a list with the following elements:

values	table with eigenvalues
coefficients	coefficients of factorial axes
components	factor coordinates

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

See Also

disqual, binarize

Examples

```
## Not run:
  # load insurance wines dataset
  data(insurance)

  # multiple correspondence analysis
  mca1 = easyMCA(insurance[,-1])
  mca1

## End(Not run)
```

FRatio *F-Statistic Ratio*

Description

Calcualtes the F-statistic between a quantitative variable and a qualitative variable

Usage

```
FRatio(variable, group)
```

Arguments

variable	a quantitative variable
group	a vector or factor with group memberships (i.e. qualitative variable)

Value

F-statistic and its p-value

Author(s)

Gaston Sanchez

References

Tenenhaus M. (2007) *Statistique*. Dunod, Paris.

See Also

discPower, corRatio

Examples

```
## Not run:
  # load bordeaux wines dataset
  data(bordeaux)

  # F-statistic ratio between temperature and quality
  FRatio(bordeaux$temperature, bordeaux$quality)

## End(Not run)
```

---

geoDA *Geometric Predictive Discriminant Analysis*

Description

Performs a Geometric Predictive Discriminant Analysis

Usage

```
geoDA(variables, group, validation = NULL, learn = NULL,
  test = NULL)
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group memberships
validation	type of validation, either "crossval" or "learntest". Default NULL
learn	optional vector of indices for a learn-set. Only used when validation="learntest". Default NULL
test	optional vector of indices for a test-set. Only used when validation="learntest". Default NULL

Details

When `validation=NULL` there is no validation
When `validation="crossval"` cross-validation is performed by randomly separating the observations in ten groups.
When `validation="learntest"` validationi is performed by providing a learn-set and a test-set of observations.

Value

An object of class `"geoda"`, basically a list with the following elements:

`functions`	table with discriminant functions
`confusion`	confusion matrix
`scores`	discriminant scores for each observation
`classification`	assigned class
`error_rate`	misclassification error rate

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

Tuffery S. (2011) *Data Mining and Statistics for Decision Making*. Wiley, Chichester.

See Also

`classify`, `desDA`, `linDA`, `quaDA`, `plsDA`

Examples

```
## Not run:
  # load bordeaux wines dataset
  data(iris)

  # geometric predictive discriminant analysis with no validation
  my_geo1 = geoDA(iris[,1:4], iris$Species)
  my_geo1$confusion
  my_geo1$error_rate

  # geometric predictive discriminant analysis with cross-validation
  my_geo2 = geoDA(iris[,1:4], iris$Species, validation="crossval")
  my_geo2$confusion
  my_geo2$error_rate
```

```
## End(Not run)
```

`getWithin` *Within-class Covariance Matrix*

Description

Calculates the estimated within-class covariance matrix

Usage

```
getWithin(variables, group)
```

Arguments

`variables`	matrix or data frame with explanatory variables (No missing values are allowed)
`group`	vector or factor with group memberships (No missing values are allowed)

Details

The obtained matrix is the estimated within-class covariance matrix (i.e. within-class covariance matrix divided by its degrees of freedom `n-k`, where `n` is the number of observations and `k` is the number of groups)

Author(s)

Gaston Sanchez

See Also

`withinCov`

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # estimated within-class covariance matrix (dividing by n-k)
  getWithin(iris[,1:4], iris[,5])

  # compared to the within-class covariance matrix (dividing by n-1)
  withinCov(iris[,1:4], iris[,5])

## End(Not run)
```

groupMeans *Group Means*

Description

Calculates means for each group

Usage

```
groupMeans(variables, group, na.rm = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (may contain missing values)
group	vector or factor with group memberships
na.rm	logical indicating whether missing values should be removed

Value

matrix of group means (with variables in the rows, and groups in the columns)

Author(s)

Gaston Sanchez

See Also

groupVars, groupStds, groupMedians, groupQuants

Examples

```
## Not run:
  # dataset iris
  data(iris)

  # group means
  groupMeans(iris[,1:4], iris[,5])

## End(Not run)
```

groupMedians *Group Medians*

Description

Calculates the medians for each group

Usage

```
groupMedians(variables, group, na.rm = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (may contain missing values)
group	vector or factor with group memberships
na.rm	logical indicating whether missing values should be removed

Value

matrix of group medians (with variables in the rows, and groups in the columns)

Author(s)

Gaston Sanchez

See Also

groupVars, groupStds, groupMeans, groupQuants

Examples

```
## Not run:
  # dataset iris
  data(iris)

  # group means
  groupMedians(iris[,1:4], iris[,5])

## End(Not run)
```

groupQuants *Group Quantiles*

Description

Calculates the specified quantiles for each group

Usage

```
groupQuants(variables, group, prob, na.rm = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (may contain missing values)
group	vector or factor with group memberships
prob	probability value (numeric value between 0 and 1)
na.rm	logical indicating whether missing values should be removed

Value

matrix of group quantiles (with variables in the rows, and groups in the columns)

Author(s)

Gaston Sanchez

See Also

groupMeans, groupVars, groupStds, groupMedians

Examples

```
## Not run:
  # dataset iris
  data(iris)

  # group quantile prob=20
  groupQuants(iris[,1:4], iris[,5], prob=0.20)

## End(Not run)
```

groupStds *Group Standard Deviations*

Description

Calculates the standard deviations for each group

Usage

```
groupStds(variables, group, na.rm = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (may contain missing values)
group	vector or factor with group memberships
na.rm	logical indicating whether missing values should be removed

Value

matrix of group standard deviations (with variables in the rows, and groups in the columns)

Author(s)

Gaston Sanchez

See Also

groupMeans, groupVars, groupMedians, groupQuants

Examples

```
## Not run:
  # dataset iris
  data(iris)

  # group standard deviations
  groupStds(iris[,1:4], iris[,5])

## End(Not run)
```

groupVars *Group Variances*

Description

Calculates the variances for each group

Usage

```
groupVars(variables, group, na.rm = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (may contain missing values)
group	vector or factor with group memberships
na.rm	logical indicating whether missing values should be removed

Value

matrix of group variances (with variables in the rows, and groups in the columns)

Author(s)

Gaston Sanchez

See Also

groupMeans, groupStds, groupMedians, groupQuants

Examples

```
## Not run:
  # dataset iris
  data(iris)

  # group variances
  groupVars(iris[,1:4], iris[,5])

## End(Not run)
```

infarctus *Infarctus dataset*

Description

Infarctus dataset from Saporta (2006)

Format

A data frame with 101 observations on the following 8 variables.

FRCAR	Frequence Cardiaque (i.e. heart rate)
INCAR	Index Cardique (cardiac index)
INSYS	Index Systolique (systolic index)
PRDIA	Pression Diastolique (diastolic pressure)
PAPUL	Pression Arterielle Pulmonaire (pulmonary artery pressure)
PVENT	Pression Ventriculaire (ventricular pressure)
REPUL	Resistance Pulmonaire (pulmonary resistance)
PRONO	Pronostic (prognosis): a factor with levels dead and survive

References

Chapter 18: Analyse discriminante et regression logistique, pp 453-454
Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

Examples

```
## Not run:
  # load data
  data(infarctus)

  # summary of variables
  summary(infarctus)

## End(Not run)
```

insurance *Insurance Dataset*

Description

Dataset of car-insurance customers from Belgium in 1992

Format

A data frame with 1106 observations on the following 10 variables.

`Claims`	Group variable. A factor with levels `bad` and `good`
`Use`	Type of Use. A factor with levels `private` and `professional`
`Type`	Insurance Type. A factor with levels `companies`, `female`, and `male`
`Language`	Language. A factor with levels `flemish` and `french`
`BirthCohort`	Birth Cohort. A factor with levels `BD_1890_1949`, `BD_1950_1973`, and `BD_unknown`
`Region`	Geographic Region. A factor with levels `Brussels` and `Other_regions`
`BonusMalus`	Level of bonus-malus. A factor with levels `BM_minus` and `BM_plus`
`YearSuscrip`	Year of Subscription. A factor with levels `YS<86` and `YS>=86`
`Horsepower`	Horsepower. A factor with levels `HP<=39` and `HP>=40`
`YearConstruc`	Year of vehicle construction. A factor with levels `YC_33_89` and `YC_90_91`

Details

Dataset for DISQUAL method

References

Saporta G., Niang N. (2006) Correspondence Analysis and Classification. In *Multiple Correspondence Analysis and Related Methods*, M. Greenacre and J. Blasius, Eds., pp 371-392. Chapman & Hall/CRC, Boca Raton, Florida, USA.

See Also

`disqual`

Examples

```
## Not run:
  # load data
  data(insurance)

  # structure
  str(insurance)

## End(Not run)
```

`linDA` *Linear Discriminant Analysis*

Description

Performs a Linear Discriminant Analysis

Usage

```
linDA(variables, group, prior = NULL, validation = NULL,
  learn = NULL, test = NULL, prob = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group memberships
prior	optional vector of prior probabilities. Default prior=NULL implies group proportions
validation	type of validation, either "crossval" or "learntest". Default NULL
learn	optional vector of indices for a learn-set. Only used when validation="learntest". Default NULL
test	optional vector of indices for a test-set. Only used when validation="learntest". Default NULL
prob	logical indicating whether the group classification results should be expressed in probability terms

Details

When validation=NULL there is no validation
When validation="crossval" cross-validation is performed by randomly separating the observations in ten groups.
When validation="learntest" validation is performed by providing a learn-set and a test-set of observations.

Value

An object of class "linda", basically a list with the following elements:

functions	table with discriminant functions
confusion	confusion matrix
scores	discriminant scores for each observation
classification	assigned class
error_rate	misclassification error rate

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

Saporta G. (2006) *Probabilites, analyse des donnees et statistique*. Editions Technip, Paris.

Tuffery S. (2011) *Data Mining and Statistics for Decision Making*. Wiley, Chichester.

See Also

classify, desDA, geoDA, quaDA, plsDA

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # linear discriminant analysis with no validation
  my_lin1 = linDA(iris[,1:4], iris$Species)
  my_lin1$confusion
  my_lin1$error_rate

  # linear discriminant analysis with cross-validation
  my_lin2 = linDA(iris[,1:4], iris$Species, validation="crossval")
  my_lin2$confusion
  my_lin2$error_rate

  # linear discriminant analysis with learn-test validation
  learning = c(1:40, 51:90, 101:140)
  testing = c(41:50, 91:100, 141:150)
 my_lin3 = linDA(iris[,1:4], iris$Species, validation="learntest", learn=learning, test=testing)
  my_lin3$confusion
  my_lin3$error_rate

## End(Not run)
```

---

plsDA *PLS Discriminant Analysis*

Description

Performs a Partial Least Squares (PLS) Discriminant Analysis by giving the option to include a random leave-k fold out cross validation

Usage

```
plsDA(variables, group, autosel = TRUE, comps = 2,
  validation = NULL, learn = NULL, test = NULL,
  cv = "LOO", k = NULL, retain.models = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group memberships
autosel	logical indicating automatic selection of PLS components by cross-validation. Default autosel=TRUE

comps	integer greater than one indicating the number of PLS components to retain. Used only when autosel=FALSE
validation	type of validation, either NULL or "learntest". Default NULL
learn	optional vector of indices for a learn-set. Only used when validation="learntest". Default NULL
test	optional vector of indices for a test-set. Only used when validation="learntest". Default NULL
cv	string indicating the type of crossvalidation. Avialable options are "LOO" (Leave-One-Out) and "LKO" (Leave-K fold-Out)
k	fold left out if using LKO (usually 7 or 10)
retain.models	whether to retain lower models (i.e. all lower component results)

Details

When validation=NULL leave-one-out (loo) cross-validation is performed.
When validation="learntest" validation is performed by providing a learn-set and a test-set of observations.

Value

An object of class "plsda", basically a list with the following elements:

functions	table with discriminant functions
confusion	confusion matrix
scores	discriminant scores for each observation
loadings	loadings
y.loadings	y loadings
classification	assigned class
error_rate	misclassification error rate
components	PLS components
Q2	quality of loo cross-validation
R2	R-squared coefficients
VIP	Variable Importance for Projection
comp_vars	correlations between components and variables
comp_group	correlations between components and groups

Author(s)

Charles Determan Jr, Gaston Sanchez

References

Tenenhaus M. (1998) *La Regression PLS*. Editions Technip, Paris.

Perez-Enciso M., Tenenhaus M. (2003) *Prediction of clinical outcome with microarray data: a partial least squares discriminant analysis (PLS-DA) approach*. Human Genetics 112: 581-592.

See Also

classify, geoDA, linDA, quaDA

Examples

```
## Not run:
# load iris dataset
data(iris)

# PLS discriminant analysis specifying number of components = 2
my_pls1 = plsDA(iris[,1:4], iris$Species, autosel=FALSE, comps=2)
my_pls1$confusion
my_pls1$error_rate
# plot circle of correlations
plot(my_pls1)

# PLS discriminant analysis with automatic selection of components
my_pls2 = plsDA(iris[,1:4], iris$Species, autosel=TRUE)
my_pls2$confusion
my_pls2$error_rate

# linear discriminant analysis with learn-test validation
learning = c(1:40, 51:90, 101:140)
testing = c(41:50, 91:100, 141:150)
my_pls3 = plsDA(iris[,1:4], iris$Species, validation="learntest",
learn=learning, test=testing)
my_pls3$confusion
my_pls3$error_rate

## End(Not run)
```

---

quaDA *Quadratic Discriminant Analysis*

Description

Performs a Quadratic Discriminant Analysis

Usage

```
quaDA(variables, group, prior = NULL, validation = NULL,
  learn = NULL, test = NULL, prob = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables
group	vector or factor with group memberships
prior	optional vector of prior probabilities. Default prior=NULL implies group proportions

validation	type of validation, either "crossval" or "learntest". Default NULL
learn	optional vector of indices for a learn-set. Only used when validation="learntest". Default NULL
test	optional vector of indices for a test-set. Only used when validation="learntest". Default NULL
prob	logical indicating whether the group classification results should be expressed in probability terms

Details

When validation=NULL there is no validation
When validation="crossval" cross-validation is performed by randomly separating the observations in ten groups.
When validation="learntest" validationi is performed by providing a learn-set and a test-set of observations.

Value

An object of class "quada", basically a list with the following elements:

confusion	confusion matrix
scores	discriminant scores for each observation
classification	assigned class
error_rate	misclassification error rate

Author(s)

Gaston Sanchez

References

Lebart L., Piron M., Morineau A. (2006) *Statistique Exploratoire Multidimensionnelle*. Dunod, Paris.

Tenenhaus G. (2007) *Statistique*. Dunod, Paris.

Tuffery S. (2011) *Data Mining and Statistics for Decision Making*. Wiley, Chichester.

See Also

classify, desDA, geoDA, linDA, plsDA

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # quadratic discriminant analysis with no validation
```

```
my_qua1 = quaDA(iris[,1:4], iris$Species)
my_qua1$confusion
my_qua1$error_rate

# quadratic discriminant analysis with cross-validation
my_qua2 = quaDA(iris[,1:4], iris$Species, validation="crossval")
my_qua2$confusion
my_qua2$error_rate

# quadratic discriminant analysis with learn-test validation
learning = c(1:40, 51:90, 101:140)
testing = c(41:50, 91:100, 141:150)
my_qua3 = quaDA(iris[,1:4], iris$Species, validation="learntest",
    learn=learning, test=testing)
my_qua3$confusion
my_qua3$error_rate

## End(Not run)
```

`totalCov` *Total Covariance Matrix*

Description

Calculates total covariance matrix

Usage

```
totalCov(variables, div_by_n = FALSE)
```

Arguments

`variables`	matrix or data frame with explanatory variables (No missing values are allowed)
`div_by_n`	logical indicating division by number of observations

Details

When `div_by_n=TRUE` the covariance matrices are divided by n (number of observations), otherwise they are divided by n-1

Author(s)

Gaston Sanchez

See Also

`totalSS`, `betweenCov`, `withinCov`

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # total covariance matrix (dividing by n-1)
  totalCov(iris[,1:4])

  # total covariance matrix (dividing by n)
  totalCov(iris[,1:4], div_by_n=TRUE)

## End(Not run)
```

---

totalSS *Total Sum of Squares Matrix*

Description

Calculates the total sum of squares and cross product matrix (a.k.a. total scatter matrix)

Usage

```
totalSS(variables)
```

Arguments

variables	matrix or data frame with explanatory variables

Author(s)

Gaston Sanchez

See Also

totalCov, betweenSS, withinSS

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # total scatter matrix
  totalSS(iris[,1:4])

## End(Not run)
```

withinCov *Within-class Covariance Matrix*

Description

Calculates the within-class covariance matrix

Usage

```
withinCov(variables, group, div_by_n = FALSE)
```

Arguments

variables	matrix or data frame with explanatory variables (No missing values are allowed)
group	vector or factor with group memberships (No missing values are allowed)
div_by_n	logical indicating division by number of observations

Details

When div_by_n=TRUE the covariance matrices are divided by n (number of observations), otherwise they are divided by n-1

Author(s)

Gaston Sanchez

See Also

withinSS, betweenCov, totalCov

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # within-class covariance matrix (dividing by n-1)
  withinCov(iris[,1:4], iris[,5])

  # within-class covariance matrix (dividing by n)
  withinCov(iris[,1:4], iris[,5], div_by_n=TRUE)

## End(Not run)
```

withinSS *Within-class Sum of Squares Matrix*

Description

Calculates within-class sum of squares and cross product matrix (a.k.a. within-class scatter matrix)

Usage

```
withinSS(variables, group)
```

Arguments

variables	matrix or data frame with explanatory variables (No missing values are allowed)
group	vector or factor with group memberships (No missing values are allowed)

Author(s)

Gaston Sanchez

See Also

withinCov, betweenSS, totalSS

Examples

```
## Not run:
  # load iris dataset
  data(iris)

  # within-class scatter matrix
  withinSS(iris[,1:4], iris[,5])

## End(Not run)
```

Index

∗ **datasets**
bordeaux, 6
infarctus, 23
insurance, 23
∗ **package**
DiscriMiner-package, 2

betweenCov, 3, *5*, *30*, *32*
betweenSS, 4, *4*, *31*, *33*
binarize, 5, *13, 14*
bordeaux, 6

classify, 7, *13*, *16*, *26*, *28, 29*
corRatio, 8, *11*, *15*

desDA, 9, *16*, *26*, *29*
discPower, *8*, 10, *10*, *15*
DiscriMiner-package, 2
disqual, *7*, 12, *14*, *24*

easyMCA, *6*, 13, *13*

FRatio, *8*, *11*, 14

geoDA, *7*, 15, *26*, *28, 29*
getWithin, *4*, *9*, 17
groupMeans, 18, *19–22*
groupMedians, *18*, 19, *20–22*
groupQuants, *18, 19*, 20, *21, 22*
groupStds, *18–20*, 21, *22*
groupVars, *18–21*, 22

infarctus, 23
insurance, 23

linDA, *7*, *16*, 24, *28, 29*

plsDA, *7*, *16*, 26, *26*, *29*

quaDA, *7*, *16*, *26*, 28, *28*

totalCov, *4*, 30, *31, 32*
totalSS, *5*, *30*, 31, *33*

withinCov, *4*, *17*, *30*, 32, *33*
withinSS, *5*, *31, 32*, 33