Package: sROC (via r-universe)

November 13, 2026

Type Package

Title Nonparametric Smooth ROC Curves for Continuous Data

Version 0.1.2.9001

Author Xiao-Feng Wang [aut, cre]

Maintainer Xiao-Feng Wang <wangx6@ccf.org>

Description A collection of functions to perform nonparametric estimation of receiver operating characteristic (ROC) curves for continuous data. Compatibility updates by Renova.

License GPL (>= 3)

Repository https://renova-r.r-universe.dev

Date/Publication 2026-11-13 17:56:36 UTC

RemoteUrl https://github.com/renova-r/sROC

RemoteRef renova-0.1.2.9001

RemoteSha 678e397ad56f2491e3d00a12b81f290bf69d16ae

Contents

AUC . . . 2
bw.CDF . . . 3
bw.CDF.pi . . . 4
CI.CDF . . . 5
kCDF . . . 6
kROC . . . 8
plot.CDF . . . 10
plot.ROC . . . 11
print.AUC . . . 12
print.CDF . . . 12
print.ROC . . . 13

Index **14**

AUC *Area Under Curve*

Description

Compute the area under curve of estimated ROC curve.

Usage

```
AUC(ROC, method="Simpson", ngrid=256)
```

Arguments

ROC	a "ROC" object generated by kROC(...).
method	a character string giving the numerical integration method to be used. This must be either "Simpson" or "Trapez".
ngrid	the number of grids for numerical integration.

Details

Compute the area under curve of estimated ROC curve.

Value

An object of class "AUC".

Author(s)

X.F. Wang <wangx6@ccf.org>

See Also

kROC.

Examples

```
set.seed(100)
n <- 200
x <- rlnorm(n, mean=2, sd=1)
y <- rnorm(n,mean=2,sd=2)

xy.ROC <- kROC(c(x,NA,NA),c(y,1.2, NA), na.rm=TRUE)
plot(xy.ROC)
AUC(xy.ROC)
```

bw.CDF *Bandwidth Selectors for Kernel CDF Estimation*

Description

Rule-of-thumb bandwidth selectors for kernel CDF estimation using the normal CDF or PDF reference approach.

Usage

```
bw.CDF(x, method="npdf")
```

Arguments

x	numeric vector.
method	either "npdf" (the normal PDF reference approach) or "ncdf" (the normal CDF reference approach).

Details

bw.CDF implements a rule-of-thumb for choosing the bandwidth of a Gaussian kernel CDF estimator.

Value

A bandwidth on a scale suitable for the bw argument of kCDF.

Author(s)

X.F. Wang <wangx6@ccf.org>

References

Altman, N., and Leger, C. (1995). Bandwidth selection for kernel distribution function estimation. *Journal of Statistical Planning and Inference*, 46, 195-214.

See Also

kCDF, bw.CDF.pi.

Examples

```
set.seed(100)
n <- 200
x <- c(rnorm(n/2, mean=-2, sd=1), rnorm(n/2, mean=3, sd=0.8))
bw.CDF(x, method="npdf")
bw.CDF(x, method="ncdf")
```

bw.CDF.pi *Plug-in Bandwidth Selectors for Kernel CDF Estimation*

Description

Plug-in bandwidth selectors for kernel CDF estimation using Altman and Leger's approach.

Usage

```
bw.CDF.pi(x, pilot="UCV")
```

Arguments

x	numeric vector.
pilot	a character string giving a rule to choose the pilot bandwidth to estimate $E(f''(x))$. There are 6 choices: The default, "ucv", implement unbiased cross-validation, "nrd0" is the Silverman's rule of thumb, "nrd" is the Scott's method (1992), "bcv" is the biased cross-validation, "sj" is the method of Sheather and Jones (1991), "onestage" is the one-stage method by Wand and Jones.

Details

bw.CDF implements a rule-of-thumb for choosing the bandwidth of a Gaussian kernel CDF estimator.

Value

A bandwidth on a scale suitable for the bw argument of kCDF.

Author(s)

X.F. Wang <wangx6@ccf.org>

References

Altman, N., and Leger, C. (1995). Bandwidth selection for kernel distribution function estimation. *Journal of Statistical Planning and Inference*, 46, 195-214.

Scott, D. W. (1992) *Multivariate Density Estimation: Theory, Practice, and Visualization.* Wiley.

Sheather, S. J. and Jones, M. C. (1991). A reliable data-based bandwidth selection method for kernel density estimation. *Journal of Royal Statistical Society Series B*, 53, 683-690.

Silverman, B. W. (1986) *Density Estimation*. London: Chapman and Hall.

Wand, M.P. and Jones, M.C. (1995) *Kernel Smoothing*. New York: Chapmon and Hall.

See Also

kCDF, bw.CDF.

Examples

```
set.seed(100)
n <- 200
x <- c(rnorm(n/2, mean=-2, sd=1), rnorm(n/2, mean=3, sd=0.8))
bw.CDF.pi(x)
bw.CDF.pi(x, pilot="nrd0")
bw.CDF.pi(x, pilot="nrd")
bw.CDF.pi(x, pilot="bcv")
bw.CDF.pi(x, pilot="sj")
bw.CDF.pi(x, pilot="onestage")
```

`CI.CDF` *Pointwise Confidence Intervals for Kernel Smooth CDF*

Description

Estimate the pointwise confidence intervals for Kernel Smooth CDF.

Usage

```
CI.CDF(CDF, alpha=0.05)
```

Arguments

`CDF`	a "CDF" object generated by kCDF(...).
`alpha`	the significant level. The default is 0.05 which generates 95% confidence intervals for the CDF.

Details

The pointwise confidence intervals are calculated by the asymptotic distribution of the kernel estimator of CDF.

Value

A list contents

`x`	the points where the CDF is estimated.
`Fhat`	the estimated CDF values. These will be numerical numbers between zero and one.
`Fhat.upper`	the upper boundaries of the CDF.
`Fhat.lower`	the lower boundaries of the CDF.
`alpha`	the significant level used.

Author(s)

X.F. Wang <wangx6@ccf.org>

References

Azzalini, A. (1981). A note on the estimation of a distribution function and quantiles by a kernel method. *Biometrika*, 68, 326-328.

Wang, X.F., Fan, Z., and Wang, B. (2010). Estimating smooth distribution function in the presence of heteroscedastic measurement errors. *Computational Statistics and Data Analysis*, 54(1), 25-36.

See Also

kCDF, bw.CDF.pi.

Examples

```
set.seed(100)
n <- 200
x <- c(rnorm(n/2, mean=-2, sd=1), rnorm(n/2, mean=3, sd=0.8))
x.CDF <- kCDF(x)
x.CDF
CI.CDF(x.CDF)
plot(x.CDF, alpha=0.05, main="Kernel estimate of distribution function")
curve(pnorm(x, mean=-2, sd=1)/2 + pnorm(x, mean=3, sd=0.8)/2, from =-6, to=6, add=TRUE, lty=2, col="blue")
```

---

kCDF *Kernel Estimation for Cumulative Distribution Function*

Description

To compute the nonparametric kernel estimate for cumulative distribution function (CDF).

Usage

```
kCDF(x, bw="pi_ucv", adjust=1, kernel=c("normal", "epanechnikov"), xgrid,
 ngrid=256, from, to, cut=3, na.rm = FALSE, ...)
```

Arguments

x	the data from which the estimate is to be computed.
bw	the smoothing bandwidth to be used. bw can also be a character string giving a rule to choose the bandwidth. See bw.CDF and bw.CDF.pi. The default used the Altman and Leger's plug-in approach with an unbiased cross-validation pilot bandwidth.
adjust	the parameter for adjusting the bandwidth. The bandwidth used for the estimate is actually adjust*bw. By default, $adjust = 1$.
kernel	a character string giving the smoothing kernel to be used. This must be either "normal" or "epanechnikov". By default, the normal kernel is used.
xgrid	the user-defined data points at which the CDF is to be evaluated. If missing, the CDF will be evaluated at the equally spaced points defined within the function.

ngrid	the number of equally spaced points at which the density is to be estimated.
from	the left-most points of the grid at which the density is to be estimated.
to	the right-most points of the grid at which the density is to be estimated
cut	by default, the values of from and to are cut bandwidths beyond the extremes of the data.
na.rm	logical; if TRUE, missing values are removed from x. If FALSE any missing values cause an error.
...	further arguments for methods.

Details

estimate the nonparametric kernel cumulative distribution function.

Value

An object of class "CDF".

x	the points where the CDF is estimated.
Fhat	the estimated CDF values. These will be numerical numbers between zero and one.
bw	the bandwidth used.
n	the sample size after elimination of missing values.
call	the call which produced the result.
data	the original data after elimination of missing values.
data.name	the deparsed name of the x argument.
has.na	logical; if TRUE, there are missing values in the original data.

The print method reports summary values on the x and Fhat components.

Author(s)

X.F. Wang <wangx6@ccf.org>

References

Nadaraya, E.A. (1964). Some new estimators for distribution functions. *Theory of Probability and its Applications*, 9, 497-500.

Altman, N., and Leger, C. (1995). Bandwidth selection for kernel distribution function estimation. *Journal of Statistical Planning and Inference*, 46, 195-214.

See Also

bw.CDF, bw.CDF.pi.

Examples

```
## --------------------
set.seed(100)
n <- 200
x <- c(rnorm(n/2, mean=-2, sd=1), rnorm(n/2, mean=3, sd=0.8))
x.CDF <- kCDF(x)
x.CDF
plot(x.CDF, alpha=0.05, main="Kernel estimate of distribution function", CI=FALSE)
curve(pnorm(x, mean=-2, sd=1)/2 + pnorm(x, mean=3, sd=0.8)/2, from =-6, to=6, add=TRUE, lty=2, col="blue")
```

---

kROC *Kernel Estimation for ROC Curves*

Description

To compute the nonparametric kernel estimate of receiver operating characteristic (ROC) Curves for continuous data.

Usage

```
kROC(x, y, bw.x="pi_ucv", bw.y="pi_ucv", adjust=1,
     kernel=c("normal", "epanechnikov"), xgrid,
     ngrid=256, from, to, cut=3, na.rm = FALSE, ...)
```

Arguments

x	numeric vector.
y	numeric vector.
bw.x	the smoothing bandwidth of x to be used. bw can also be a character string giving a rule to choose the bandwidth. See bw.CDF and bw.CDF.pi. The default used the Altman and Leger's plug-in approach with an unbiased cross-validation pilot bandwidth.
bw.y	the smoothing bandwidth of y to be used.
adjust	the parameter for adjusting the bandwidth. The bandwidth used for the estimate is actually adjust*bw. By default, $adjust = 1$.
kernel	a character string giving the smoothing kernel to be used. This must be either "normal" or "epanechnikov". By default, the normal kernel is used.
xgrid	the user-defined data points at which the CDF is to be evaluated. If missing, the CDF will be evaluated at the equally spaced points defined within the function.
ngrid	the number of equally spaced points at which the density is to be estimated.
from	the left-most points of the grid at which the density is to be estimated.
to	the right-most points of the grid at which the density is to be estimated
cut	by default, the values of from and to are cut bandwidths beyond the extremes of the data.

na.rm	logical; if TRUE, missing values are removed from x. If FALSE any missing values cause an error.
...	further arguments for methods.

Details

estimate the nonparametric kernel estimate of receiver operating characteristic (ROC) Curves for continuous data

Value

An object of class "ROC".

FPR	the false positive rate.
TPR	the true positive rate.
bw.x, bw.y	the bandwidths used.
nx, ny	the sample sizes after elimination of missing values.
call	the call which produced the result.
x.data.name, y.data.name	the deparsed names of the x argument.
x.has.na, y.has.na	logical; if TRUE, there are missing values in the original data.

The print method reports summary values on the x and Fhat components.

Author(s)

X.F. Wang <wangx6@ccf.org>

References

Lloyd, C.J. (1998). Using smoothed receiver operating characteristic curves to summarize and compare diagnostic systems. *Journal of the American Statistical Association*, 93(444): 1356-1364.

Zhou, X.H. and Harezlak, J. (2002). Comparison of bandwidth selection methods for kernel smoothing of ROC curves. *Statistics in Medicine*, 21, 2045-2055.

Zou, K.H., Hall, W.J., and Shapiro, D.E. (1997). Smooth non-parametric receiver operating characteristic (ROC) curves for continuous diagnostic tests. *Statistics in medicine*, 16(19): 2143-56.

See Also

bw.CDF, bw.CDF.pi.

Examples

```
## --------------------
set.seed(100)
n <- 200
x <- rgamma(n,2,1)
y <- rnorm(n)

xy.ROC <- kROC(x,y, bw.x="pi_sj",bw.y="pi_sj")
xy.ROC

plot(xy.ROC)
```

`plot.CDF` *Plot a CDF Object*

Description

To plot a "CDF" object generated by `kCDF(...)`.

Usage

```
 ## S3 method for class 'CDF'
plot(x, CI=TRUE, alpha=0.05, main = NULL, xlab = NULL, ylab = "CDF", lwd=2, lty=1, ...)
```

Arguments

`x`	a "CDF" object generated by `kCDF(...)`.
`CI`	If TRUE, the pointwise confidence intervals will be plotted.
`alpha`	the significant level. The default is 0.05 which generates 95% confidence intervals for the CDF.
`main`	see `par`
`xlab`	see `par`
`ylab`	see `par`
`lwd`	see `par`
`lty`	see `par`
`...`	further arguments for the plot function.

Details

This function is to plot the estimated function generated by `kCDF(...)`

Author(s)

X.F. Wang <wangx6@ccf.org>

See Also

kCDF.

---

plot.ROC *Plot a ROC Object*

Description

To plot a "ROC" object generated by kROC(...).

Usage

```
 ## S3 method for class 'ROC'
plot(x, main = NULL, diagonal = TRUE, xlab = "FPR", ylab = "TPR", type = "l", lwd=2, ...)
```

Arguments

x	a "ROC" object generated by kROC(...).
diagonal	if TRUE, the diagonal line will be plotted.
main	see par
xlab	see par
ylab	see par
type	see par
lwd	see par
...	further arguments for the plot function.

Details

This function is to plot the estimated function generated by kROC(...)

Author(s)

X.F. Wang <wangx6@ccf.org>

See Also

kROC.

print.AUC *Print a AUC Object*

Description

To print a "AUC" object generated by `AUC(...)`.

Usage

```
 ## S3 method for class 'AUC'
print(x, digits = NULL, ...)
```

Arguments

`x`	a "AUC" object generated by `AUC(...)`.
`digits`	integer indicating the number of decimal places to be used.
`...`	further arguments for the print function.

Details

This function is to print the summary description from the object generated by `AUC(...)`

Author(s)

X.F. Wang `<wangx6@ccf.org>`

See Also

`AUC`.

print.CDF *Print a CDF Object*

Description

To print a "CDF" object generated by `kCDF(...)`.

Usage

```
 ## S3 method for class 'CDF'
print(x, digits = NULL, ...)
```

Arguments

x	a "CDF" object generated by kCDF(...).
digits	integer indicating the number of decimal places to be used.
...	further arguments for the print function.

Details

This function is to print the summary description from the object generated by kCDF(...)

Author(s)

X.F. Wang <wangx6@ccf.org>

See Also

kCDF.

---

print.ROC *Print a ROC Object*

Description

To print a "ROC" object generated by kROC(...).

Usage

```
 ## S3 method for class 'ROC'
print(x, digits = NULL, ...)
```

Arguments

x	a "ROC" object generated by kROC(...).
digits	integer indicating the number of decimal places to be used.
...	further arguments for the print function.

Details

This function is to print the summary description from the object generated by kROC(...)

Author(s)

X.F. Wang <wangx6@ccf.org>

See Also

kROC.

Index

∗ **distribution function estimation**
  kCDF, 6
∗ **nonparametric**
  kCDF, 6
  kROC, 8
∗ **smoothing**
  AUC, 2
  bw.CDF, 3
  bw.CDF.pi, 4
  CI.CDF, 5
  plot.CDF, 10
  plot.ROC, 11
  print.AUC, 12
  print.CDF, 12
  print.ROC, 13
∗ **smooth**
  kCDF, 6
  kROC, 8

AUC, 2, *12*

bw.CDF, 3, *4*, *6–9*
bw.CDF.pi, *3*, 4, *6–9*

CI.CDF, 5

kCDF, *3, 4*, 6, *6*, *11*, *13*
kROC, *2*, 8, *11*, *13*

par, *10, 11*
plot.CDF, 10
plot.ROC, 11
print.AUC, 12
print.CDF, 12
print.ROC, 13

summary, *7*, *9*