Package: vader (via r-universe)

November 13, 2026

Title Valence Aware Dictionary and sEntiment Reasoner (VADER)

Version 0.2.1.9001

Description A lexicon and rule-based sentiment analysis tool that is specifically attuned to sentiments expressed in social media, and works well on texts from other domains. Hutto & Gilbert (2014) <https://www.aaai.org/ocs/index.php/ICWSM/ICWSM14/paper/view/8109/8122>. Compatibility updates by Renova.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Imports tm

Depends R (>= 2.10)

Suggests spelling

Language en-US

NeedsCompilation no

Author Katherine Roehrick [aut, cre]

Maintainer Katherine Roehrick <kr.gitcode@gmail.com>

Config/pak/sysreqs libxml2-dev

Repository https://renova-r.r-universe.dev

Date/Publication 2026-11-13 17:53:52 UTC

RemoteUrl https://github.com/renova-r/vader

RemoteRef renova-0.2.1.9001

RemoteSha b264a5a2a6483c00db580b1a2481bc53cc33baa9

Contents

get_vader 2
vader_df 3

Index 5

`get_vader` *Get a named vector of vader results for a single text document*

Description

Use get_vader() to calculate the valence of a single text document.

Usage

```
get_vader(text, incl_nt = T, neu_set = T, rm_qm = T)
```

Arguments

`text`	to be analyzed; for get_vader(), the text should be a character string
`incl_nt`	defaults to T, indicates whether you wish to incl UNUSUAL n't contractions (e.g., yesn't) in negation analysis
`neu_set`	defaults to T, indicates whether you wish to count neutral words in calculations
`rm_qm`	defaults to T, indicates whether you wish to clean quotation marks from text (setting to F may result in errors)

Value

A named vector containing the valence score for each word; an overall, compound valence score for the text; the weighted percentage of positive, negative, and neutral words in the text; and the frequency of the word "but".

References

For the original Python Code, please see:

- https://github.com/cjhutto/vaderSentiment
- https://github.com/cjhutto/vaderSentiment/blob/master/vaderSentiment/vaderSentiment.py

For the original R Code, please see:

- https://github.com/nrguimaraes/sentimentSetsR/blob/master/R/ruleBasedSentimentFunctions.R

Modifications to the above scripts include, but are not limited to:

- ALL CAPS fx: updated to account for non-alpha words; i.e. "I'M 100 PERCENT SURE" would previously have been counted as mixed case due to the use of numbers
- IDIOMS fx: added capacity to check for idioms that do not contain any words found in the Vader Lexicon
- WORDS+EMOT: strip punctuation while preserving ALL emoticons found in dictionary
- Option to turn on/off neutral count

N.B.

In the examples below, "yesn't" is an internet neologism meaning "no", "maybe yes, maybe no", "didn't", etc.

See Also

vader_df to get vader results for multiple text documents

Examples

```
get_vader("I yesn't like it")
get_vader("I yesn't like it", incl_nt = FALSE)
get_vader("I yesn't like it", neu_set = FALSE)
get_vader("I said \"I'm not happy\"", rm_qm = FALSE)
get_vader("I said \" I'm not happy \" ", rm_qm = FALSE)
```

---

vader_df *Get a dataframe of vader results for multiple text documents*

Description

Use vader_df() to calculate the valence of multiple texts contained within a vector or column in a dataframe.

Usage

```
vader_df(text, incl_nt = T, neu_set = T, rm_qm = F)
```

Arguments

text	to be analyzed; for vader_df(), the text should be a single vector (e.g. 1 column)
incl_nt	defaults to T, indicates whether you wish to incl UNUSUAL n't contractions (e.g., yesn't) in negation analysis
neu_set	defaults to T, indicates whether you wish to count neutral words in calculations
rm_qm	defaults to T, indicates whether you wish to clean quotation marks from text (setting to F may result in errors)

Value

A dataframe containing the valence score for each word; an overall, compound valence score for the text; the weighted percentage of positive, negative, and neutral words in the text; and the frequency of the word "but".

N.B.

In the examples below, "yesn't" is an internet neologism meaning "no", "maybe yes, maybe no", "didn't", etc.

See Also

get_vader to get vader results for a single text document

Index

get_vader, 2, *4*

vader_df, 3, *3*